



US006956300B2

(12) **United States Patent**
Gizara

(10) **Patent No.:** **US 6,956,300 B2**
(45) **Date of Patent:** **Oct. 18, 2005**

(54) **GIMBAL-MOUNTED HYDROELECTRIC TURBINE**

(76) Inventor: **Andrew Roman Gizara**, 24471 Corta Cresta Dr., Lake Forest, CA (US) 92630-3914

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 149 days.

(21) Appl. No.: **10/604,601**

(22) Filed: **Aug. 4, 2003**

(65) **Prior Publication Data**

US 2005/0029817 A1 Feb. 10, 2005

(51) **Int. Cl.⁷** **F03B 13/10**; F03B 13/12; H02P 9/04; F03C 5/02

(52) **U.S. Cl.** **290/43**; 290/42; 290/44; 290/53; 290/54; 290/55; 60/398

(58) **Field of Search** 290/42-44, 53-55; 60/398

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,455,159 A	*	7/1969	Gies, Sr.	73/170.16
3,644,052 A	*	2/1972	Linger	415/7
3,687,567 A	*	8/1972	Linger	415/7
3,818,703 A	*	6/1974	Lapeyre	60/504
3,818,704 A	*	6/1974	Lapeyre	60/504
3,980,894 A	*	9/1976	Vary et al.	290/54
4,034,231 A	*	7/1977	Conn et al.	290/53
4,039,847 A	*	8/1977	Diggs	290/42
4,048,512 A	*	9/1977	Wood	290/53
4,060,344 A	*	11/1977	Ootsu	417/330
4,078,382 A	*	3/1978	Ricafraña et al.	60/398
4,151,424 A	*	4/1979	Bailey	290/54
4,159,427 A	*	6/1979	Wiedemann	290/55
4,170,738 A	*	10/1979	Smith	290/42
4,172,689 A	*	10/1979	Thorsheim	415/7
4,216,655 A	*	8/1980	Ghesquiere	60/398
4,256,970 A	*	3/1981	Tomassini	290/53

4,258,270 A	*	3/1981	Tornkvist	290/53
4,266,403 A	*	5/1981	Hirbod	60/698
4,313,059 A	*	1/1982	Howard	290/54
4,327,296 A	*	4/1982	Weyers	290/53
4,327,297 A	*	4/1982	Harrison	290/53
4,335,319 A	*	6/1982	Mettersheimer, Jr.	290/54
4,352,023 A	*	9/1982	Sachs et al.	290/42
4,369,375 A	*	1/1983	Romano	290/53

(Continued)

Primary Examiner—Darren Schuberg

Assistant Examiner—Pedro J. Cuevas

(57) **ABSTRACT**

A power plant extracts energy from a free flowing motive fluid by means of a turbine mounted on a gimbal. The shroud element of the fluid intake has external rudders, in conjunction with the gimbal mounting, enabling the enclosed turbine to instantaneously respond to changes in the direction of the free flowing motive fluid thus ensuring the face area of the intake is always physically orthogonal to the direction of the motive fluid streamlines. The shroud element may also be buoyant so as to optimally extract energy from an upper non-turbulent and higher velocity layer of the free flowing motive fluid. To function within an inherently unsteady source of energy, the preferred embodiment of the turbine is coupled to a DC generator which may further be coupled to a voltage and current regulating circuit which either charges a battery, performs electrolysis of water to produce hydrogen fuel, or is further coupled to a DC motor coupled to an AC generator. Alternatively an AC induction generator may be coupled to the turbine. Other mechanical, electrical, electronic, or electromechanical features may optionally be implemented to perform such tasks as adaptively locating the turbine in the maximum velocity flow, adapting internal vane and runner blade pitches for various flow rates and loads, keeping the intake free of obstructions, preventing loss of aquatic life, controlling and communicating the state of charge of the battery, or gauging and controlling the electrolysis process and communicating the fullness of the hydrogen gas output tanks.

9 Claims, 8 Drawing Sheets

